

ES1000

1U 24-port / 48-port 1GbE (PoE) Access Switch



The Celestica ES1000 is a 1U 24-port / 48-port 1GbE enterprise access switch. It is ideal for organizations looking for cost-effective scalable switches for the enterprise edge including: enterprise aggregation, campus, retail, DCN management and IoT.

ES1000 provides 24x or 48x 1000Base-T and 4x 25GbE SFP28 ports in support of enterprise access, edge and data center management applications. The platform includes high-reliability features such as redundant fixed fans and hot swappable power supplies. ES1000 is available in both forward and reverse airflow configurations with optional 90W per port PoE++ support.

The ES1000 is ideal for:

- Enterprise / SMB Access Networks
- Converged Wired / Wireless LAN
- Campus / Branch / IOT Gateways
- Management and Connectivity

FEATURES

Marvell AC5X switch chipset

Up to 148Gbps non-blocking switching capacity

Integrated A55 ARM CPU, 2C 1.5GHz

Optional: Intel Denverton x86 CPU, 4C at 2.1GHz

Memory: 8GB up to 16GB DDR4, 32 or 64GB M.2 SSD

Encryption: 256b MACsec

24 / 48 ports 1000Base-T (RJ45)

Optional: IEEE 802.3 af / at / bt, Type 4, Class 8

enabled RJ45 ports

4 ports 1GbE / 10GbE / 25GbE (SFP28)

RJ45 console and Combo / SFP OOB Ethernet

management ports

Persistent POE

2x USB 3.0 Type A interfaces

1+1 hot swappable AC PSUs with 0:1 / 1:1 mode of operations

3+1 fixed fans

ROHS Compliant



PHYSICAL DIMENSIONS

Height: 43.4 mm (1U)

Width: 438.2 mm Depth: 371.6 mm

ENVIRONMENTAL: OPERATING

Temperature: 0°C to 45°C @ 900m

Non-operating Temperature: -40°C to 60°C

Altitude: 3050m maximum. Derate ambient 1C / 175m

above 900m

ORDER INFORMATION

ES1000-24P: 24X 1GBE, ARM 2C CPU, POE++

ES1000-48P: 48X 1GBE, ARM 2C CPU, POE++

ES1000-48CP: 48X 1GBE, x86 4C CPU, POE++

ES1000-24: 24X 1GBE, ARM 2C CPU

ES1000-48: 48X 1GBE, ARM 2C CPU

ES1000-48C: 48X 1GBE, x86 4C CPU

Note: All specifications and figures are subject to change without prior notice.

